MT2500 Series Two Layer ESD Table Mat

Protect your sensitive items as well as your work surface with durable ESD matting.

The 2500 series ESD control mats from Transforming Technologies are made of a durable 0.060"thick rubber. A conductive

layer backs the static dissipative top layer that creates outstanding electrical performance characteristics. The 2500 series offers excellent resistance to hot solders, soldering irons and most solvents.

MT2500 is available in rolls or cut mats. Cut mats are packaged individually with 10mm snaps and a common point ground cord. Full rolls are 50ft long and can be easily cut with a utility knife to fit your unique workstation. Available in NASA blue, royal blue and gray colors.

Meets or exceeds requirements of ANSI ESD-S20.20 and the recommendations of ESD 4.1.



Features

- Two Layer Rubber: 10^6-10^8 Rtt
- Excellent Resistance to Hold Solders,
 Soldering Irons and Most Solvents
- Available in 50ft rolls or an assortment of ready made table mats.
- Colors: Nasa Blue, Royal Blue and Gray

Applications:

Creates an ESD safe work area by a providing a path-to-ground for electrical charges as well as protecting the work surface from damage.

Specifications:		Part Numbers:		Part Numbers:	
Thickness	0.060"	Full Rolls		Cut Mats	
Hardness	60 Shore A	MT2524B	Roll Nasa Blue, 24" x 50' x .060"	MTLP2436	Mat, 24" x 36"x .060", Hardware
Tensile Strength	>1000 PSI	MT2524RB	Roll Royal Blue, 24" x 50' x .060"	MTLP2448	Mat, 24" x 48"x .060", Hardware
Elongation	>300%	MT2524GY	Roll Gray, 24" x 50' x .060"	MTLP2460	Mat, 24" x 60"x .060", Hardware
Temperature	190F (87C)	MT2530B	Roll , Nasa Blue, 30" x 50' x .060"	MTLP2472	Mat, 24" x 72"x .060", Hardware
Color	Nasa Blue, Gray, Royal Blue	MT2530RB	Roll , Royal Blue, 30" x 50' x .060"	MTLP3648	Mat, 36" x 48"x .060", Hardware
Rubber	Premium NBR	MT2530GY	Roll, Gray, 30" x 50' x .060"	MTLP3672	Mat, 36" x 72"x .060", Hardware
RTG	8 x 10 ^{6 -8} ohms	MT2536B	Roll , Nasa Blue, 36" x 50' x .060"		
RTT	2 x	MT2530RB	Roll , Royal Blue, 36" x 50' x .060"	Shipping Dimensions and Weights	
10 ^{6 -8} ohms Charge Decay		MT2536GY	Roll, Gray, 36" x 50' x .060"	Roll, 24"x50":	45lbs - 25"x 8"x 8"
	0.01Seconds			Roll, 30"x50':	57lbs - 31"x 8"x 8"
Work surface	10^6 - 10^8 ohms Rtt			Roll, 36"x50':	69lbs - 37"x 8"x 8"
Slows charge removal; meets minimum recommended work surface requirements of ANSI/ESD S20.20					
and recommendations of ESD 4.1					

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.