



Features

- Designed to safely store both reels and Rail/DIP tubes in the same bin box
- Available in open style with better loading from above
- Available in closed style with better loading from front
- May be used for storing, kitting, or transporting during work-in-process operations
- Shipped knocked-down; easy to assemble
- Made in America

Item	Size O.D. - L x W x D (IN)
37130	Open: 18 x 2 x 9
37132	Open: 18 x 4 x 9
37134	Open: 18 x 6 x 9
37131	Open: 24 x 2 x 9
37133	Open: 24 x 4 x 9
37135	Open: 24 x 6 x 9
37611	Closed: 24-3/8 x 4-11/16 x 15-1/4

Unless otherwise noted, tolerance is $\pm 10\%$

Meets the required limits of ANSI/ESD S20.20, Packaging standard ANSI/ESD S541, and worksurface standard ANSI/ESD S4.1

SPECIFICATIONS

Properties

Surface Resistance

Sloughing Test

Recyclability

Typical Values

1×10^6 to $< 1 \times 10^9$ ohms

Negligible surface damage at 10 cycles and $< 5\%$ of surface damage at 200 cycles in Taber Abrasion Test.

No conductive particles abraded from surface

Complete recyclability of package

Test Procedures/Method

ANSI/ESD STM11.11

ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load

Rockwell International Test Report of January 8, 1992

Rockwell International Test Report of January 8, 1992

RoHS, REACH, and Conflict Minerals Statement:

See the Desco Industries ROHS, Reach and Conflict Minerals Statement
Descoindustries.com/ROHS3.aspx

See the Protektive Pak Limited Warranty
Protektivepak.descoindustries.com/Limited-Warranty.aspx



Made in the
United States of America

Specifications and procedures subject to change without notice.

REEL/DIP TUBE BIN BOXES

TEXAS TECHNOLOGIES, INC.

www.texastechnologies.com
 512.267.0100 e-mail: info@texastechnologies.com

DRAWING NUMBER
37130

DATE:
December
2018