



*Tray sold separately

Features

- Finger notches in lids for easy lifting
- Constructed of impregnated corrugated material for greater durability
- Static dissipative surface Resistance of 1×10^6 to $< 1 \times 10^9$ ohms
- Buried shielding layer minimizes the potential of sloughing and abrasion contamination
- Made from 100% recycled material and is 100% recyclable
- Made in the United States of America

Part Number	For Use With
37766	37750
37767	37760 & 37762
37768	37751
37769	37761 & 37763

Meets the required limits of ANSI/ESD S20.20, and Packaging standard ANSI/ESD S541.

SPECIFICATIONS

Properties

Surface Resistance

Sloughing Test

Recyclability

Typical Values

1×10^6 to $< 1 \times 10^9$ ohms

Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test.

No conductive particles abraded from surface

Complete recyclability of package

Test Procedures/Method

ANSI/ESD STM11.11

ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load

Rockwell International Test Report of January 8, 1992

Rockwell International Test Report of January 8, 1992



Made in the United States of America

Specifications and procedures subject to change without notice.

DROP IN LID, TEK-TRAY

TEXAS TECHNOLOGIES, INC.

www.texastechnologies.com

e-mail: info@texastechnologies.com

TEXAS TECHNOLOGIES, INC.

DRAWING NUMBER
37766

DATE:
August
2015