

Texas Technologies, Inc.
Proudly Partnering with UltraTape

3600 W. Whitestone Blvd. Cedar Park, TX 78613
800.858.1379 or 512.267.0100
E-Mail: info@texastechnologies.com
www.texastechnologies.com

PRODUCT DATASHEET

UT1114 Polyethylene Low Adhesion Perforated Cleanroom Tape

DESCRIPTION

UltraTape 1114P is a low adhesion, highly conformable polyethylene tape with perforation for ease of one-hand application. This tape is ideal for environments where protective garments are worn, creating a seal between the glove and garment.

PROPERTIES

- Easy to apply and remove with one hand.
- Excellent ability to conform to uneven surfaces and create better seals.
- Perforated every 3 inches
- Available Irradiated

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

Backing	Low Density Polyethylene
Adhesive	Acrylic
Elongation	500%
Backing Thickness	4.5 mils/.114 mm
Adhesive Thickness	1.0 mil/.025 mm
Adhesion to Stainless	12 oz/in (1.31 N/cm)
Operating Temperature	-40°F to 190°F (-40°C to 88°C)
Tensile Strength	12 lbs./in (21.02 N/cm)
Length	36 yards
Colors	White (WH)