Texas Technologies, Inc. Proudly Partnering with UltraTape

3600 W. Whitestone Blvd. Cedar Park, TX 78613 800.858.1379 or 512.267.0100

E-Mail: <u>info@texastechnologies.com</u> <u>www.texastechnologies.com</u>

PRODUCT DATASHEET

UT1167 Vinyl Anti-Skid Cleanroom Tape

DESCRIPTION

UltraTape 1167/ 0167 tape is a vinyl anti-skid tape specifically designed for use in a cleanroom. This product consists of dimensionally stable plastic film coated with a textured resilient surface. The reverse side is coated with a pressure sensitive adhesive.

PROPERTIES

- Chemical resistant
- Low profile
- Extremely durable
- Dimensionally Stable

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

Backing	Embossed Vinyl
Adhesive	Acrylic
Release Liner	N/A
Total Thickness	45 mils (1.14mm)
Minimum Application Temperature	40°F (4°C)
Adhesion to Stainless Steel	44 oz/in. (1.25 kg/25mm)
Maximum Service Temperature	175°F (79°C)
Length	20 yards
Colors	Black (BK), Gray (GY)