

Texas Technologies, Inc.
Proudly Partnering with UltraTape

3600 W. Whitestone Blvd. Cedar Park, TX 78613
800.858.1379 or 512.267.0100
E-Mail: info@texastechnologies.com
www.texastechnologies.com

PRODUCT DATASHEET

UT4440 Yellow ‘ESD CAUTION’ Overlaminated Identification Tape

DESCRIPTION

UltraTape 4440 / 0440 “ESD Caution” printed tape provides excellent floor marking, wall marking, equipment marking and labeling. This printed PVC film is overlaminated to withstand heavy floor traffic and increase chemical resistance.

PROPERTIES

- High initial tack, shear and adhesion
- Residue free
- Available in UltraClean version
- Good chemical resistance

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

Backing	PVC Vinyl Film
Overlamine	Polypropylene
Adhesive	Acrylic
Total thickness	4.0 mils (0.11 mm)
Adhesion to Stainless	43.2 oz/in
Operating Temperature	-65°F to 200°F (-54°C to 94°C)
Elongation	500%
Length	36 yards
Colors	Yellow with Black Text “ESD Caution”