Texas Technologies, Inc.

Proudly Partnering with UltraTape

3600 W. Whitestone Blvd. Cedar Park, TX 78613
800.858.1379 or 512.267.0100
E-Mail: info@texastechnologies.com
www.texastechnologies.com

PRODUCT DATASHEET

UT1188 Sub Zero Over Laminated Floor Marking Cleanroom Tape

DESCRIPTION

UltraTape 1188 tape is a vinyl stock with freezer grade acrylic adhesive. The unique adhesive formula and face stock combined with an over laminate layer allow for application at below freezing temperatures as well as moisture resistance, solvent resistance and high durability.

PROPERTIES

- Can be applied at below freezing temperatures
- Moisture resistant adhesive
- Highly durable face stock over laminate combination
- Excellent conformability

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

Backing	Vinyl with PET Clear Overlaminate
Adhesive	Acrylic
Release Liner	Calendared Kraft Paper or Self wound
Backing Thickness	4.6 mils (0.117 mm)
Adhesive Thickness	1.0 mil (0.025mm)
Adhesion to Stainless Steel	32 oz/in. (0.907 kg/25mm)
Operating Temperature	-40ºF to 140ºF (-40ºC to 60ºC)
Application Temperature	0ºF to 120ºF (-18ºC to 49ºC
Length	18 yards