

# ElectriCorr® VpCI®-239 Multi-Metal Cleaner/Protector

## DESCRIPTION

ElectriCorr® VpCI®-239 is a multifunctional outdoor cleaner/corrosion protector. It removes oils, grime, wax, and other contaminants with ease, and provides corrosion protection to the treated surface at the same time. ElectriCorr® VpCI®-239 forms a very thin film against aggressive conditions including industrial, marine, and tropical regions. The vapor phase inhibitors continuously sublime to protect difficult-to-access areas. ElectriCorr® VpCI®-239 can be safely used with most plastics, elastomers, and other non-metallics. Parts and equipment treated with ElectriCorr® VpCI®-239 and packaged properly afterwards are ready to be deployed at moments notice.

ElectriCorr® VpCI®-239 is free of CFCs and 1,1,1-Trichlorethane. Provides instant corrosion protection.

UFI: 3A20-H08X-K003-H2KY

## PACKAGING & STORAGE

ElectriCorr® VpCI®-239 is available in 9.45 oz. (267.75 grams) aerosol spray (6 cans per carton), 5 gallon (19 L) pails, 55 gallon (208 L) drums, liquid totes, and bulk

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 3 years

## VpCI® EMITTING SYSTEMS & ELECTRONIC PRODUCTS



## FEATURES

- Excellent outdoor protection
- Can be applied indoors
- Fast-drying, nonsticky corrosion inhibiting film
- Effective cleaner for grime, oil, wax, and other contaminants
- Instant corrosion protection to ferrous and non-ferrous metals
- Minimized field service
- Increased corrosion protection at a lower cost than conventional rust preventives
- CFC and 1,1,1-Trichlorethane free
- Vapor phase protection in difficult to reach areas
- Moisture-displacing and penetrating film characteristics

## TYPICAL APPLICATIONS

- Preservation of cleaned surfaces, parts, and equipment
- De-watering after aqueous cleaning
- Protection between processing steps
- Preservation of pumps
- Preservation of electric motors
- Can be used in contact with engineering plastics, elastomers, and other non-metallics
- Outdoor generators and junction boxes
- Outdoor and indoor electrical outlets

## APPLICATION

Spray a very light mist over the area needing protection. Dry time is approximately 1-2 hours at 70 °F (21 °C) and 50% relative humidity.

*Note: Application of a heavy mist will result in a heavy film that sags and remains wet.*

# ElectriCorr® VpCI®-239 Multi-Metal Cleaner/Protector

---

## STANDARD TEST METHODS

ASTM D-1748	Humidity Cabinet	300+ Hours
-------------	------------------	------------

### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

Revised: 03/02/21. Supersedes: 07/13/17. ©Cortec Corporation 2021 of Cortec® Corporation. All Rights Reserved. Copying and/or manipulation of these materials in any form without the written authorization of Cortec® Corporation is strictly prohibited. 2021, ©Cortec® Corp. ISO accreditation applies to Cortec's processes only.

DISTRIBUTED BY:

**TEXAS TECHNOLOGIES, INC.**

3600 W. Whitestone Blvd. Cedar Park, TX 78613

800.858.1379 or 512.267.0100

E-Mail: [info@texastechnologies.com](mailto:info@texastechnologies.com)

[www.texastechnologies.com](http://www.texastechnologies.com)