



M-532

DESCRIPTION

M-532 is an oil-based package of corrosion inhibitors for petroleum and synthetic lubricants. M-532 is a recommended additive to be used in a final product that goes into a system containing mostly yellow metals. M-532 is a version of M-531 that is non-aggressive to yellow metals.

FEATURES

- Excellent contact corrosion protection (no vapor phase corrosion protection)
- Excellent non-staining properties
- Typically suitable for intermittent use and operating conditions
- Resists gelling when contaminated with water

DOSING GUIDELINES

M-532 starting dosage range for various applications is 0.5%-10.0% by weight (dependent on application, length of protection, and harshness of environmental conditions).

TYPICAL PROPERTIES

| | |
|----------------------|-------------------------------------|
| Appearance | Clear amber to brown viscous liquid |
| Density | 7.8 lb/gal |
| Non-volatile Content | 97% |

APPLICATION

- Additive for industrial lubricants where excellent rust protection, filterability, and water resistance are required.
- In rust preventative applications, particularly useful for coiled steel or stacked parts due to its outstanding non-staining properties.
- Additive for hydraulic fluids; ideally suited for formulating paper machine oils and circulating oils where good filterability, anticorrosion, thermal stability, and demulsification properties are required.

PACKAGING & STORAGE

M-532 is available in 5 gallon (19 L) pails and 55 gallon (208 L) metal drums. Store in a cool, less than 115F (46C), dry place away from any direct source of heat and moisture. M-532 should be sealed before storage.

Shelf life: 2 years

SOLUBILITY

Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Last Reviewed:1/14/2026. ©2025 Cortec® Corporation. All Rights Reserved. Unauthorized copying and/or manipulation of these materials, in any form, is strictly prohibited without the prior written authorization of Cortec® Corporation. ISO accreditation applies solely to Cortec® processes.

DISTRIBUTED BY:

TEXAS TECHNOLOGIES, INC.

3600 W. Whitestone Blvd. Cedar Park, TX 78613

800.858.1379 or 512.267.0100

E-Mail: info@texastechnologies.com

www.texastechnologies.com